SECRET

	The File	*	12 September 1955					
			ORIG COMP Q ORIG CLASS <u> </u>	33 OPI3 S_ pages _3_	AY BY 01837 A TYPE 02 ASY CLASS C	23	50X1	
	Trip Rep	ort, Contr	act	T.O. VI, w	i th		50X1 50X1	
and	1. At		te on 9 Se to conjunct:	on with	5 by Task Order	VI.	50X1 50X1 50X1	
		Satisfac equipmen readied etc.	tory work t measures to permit has a	ents; traile field equips dvised	complished as : or units are be sents being in	ring stalled,	50X11 50X1	
		United States ordered desired	tates Air ers which	Force has pl will prevent without Depo	p-film CRT cem aced priority make artment of Defe	procure- ing	50X1 _.	
		necessar.	y priority	procurement	requested to proper of two each ()		50X1 50X1	
	c.	officer data to	permit the	yet provide return of t	rised that come the collins 51 ipment to cont	y shipping J() re-	50X1	
	đ.	PMO osci.	llator uni	ts being ass by reason t	authorise throigned to this that the PMO or obnson By ampl	project itput		

SECRET

CONFIDENTIAL

-SECRET

Page 2

12 September 1955

50X1

50X1

50X1

50X1 50X1

a. TO-VI, is the investigation of certain equipment arrangements and the measurements pertaining thereto. The end result will be certain knowledge upon which an operational system may be beselor alternately the limitation beyond which the system cannot be established for operational assignments. b. In this consection, sware of the inherent bandwidth requirements of the test units currently conceived. Little factual consideration has been taken towards the reduction of these acute problems. It has been, therefore, measurement of the equipments to permit the establishment of valid measurements with which the Agency can then program into the necessary parameters for an operational acceptable system. 4. Future Action: a. For the purpose of conduction of the test, has been advised: (1) (In consideration of prior frequency data coordinated with AAB) to establish BCB terminal to operate at center-frequency \(\frac{1}{2}\) hose been advised: (2) (In consideration of prior frequency data center frequency (nime 10 km) band 3155-3240 km; field site one to operate at center frequency (plus 10 km) band 3155-3240 km; field site two to operate at center frequency (plus 10 km) band 3155-3240 km; field site two to operate at center frequency (plus 10 km) band 3155-3240 km; field site two to operate at center frequency (plus 10 km) band 3155-3240 km; field site two to operate at center frequency (plus 10 km) band 3155-3240 km; field site two to operate at center frequency (plus 10 km) band 3155-3240 km; field site one to operate at center frequency in the provide necessary backstop with FCC in this regard. 5. Notus operandi: a. For test measurement purposes HCS will treasure: (1) A sine wave ready signal.	3.	Duta	for record purposes:					
thereto. The end result will be certain knowledge upon which an operational system may be based—or alternately the limitation beyond which the system cannot be established for operational assignments. b. In this connection,		a.						
alternately the limitation beyond which the system cannot be established for operational assignments. b. In this connection, mears of the inherent bandwidth requirements of the test units currently conceived. Little factual consideration has been taken towards the reduction of these acute problems. It has been, therefore, mosessary for the Agency representatives to confine for Task Order VI, to the arrangement of the equipments to parmit the establishment of valid measurements with which the Agency can then program into the necessary parameters for an operational acceptable system. 4. Future Action: a. For the purpose of conduction of the test, has been advised: (1) (In consideration of prior frequency data coordinated with AMB) to establish MCB terminal to operate at center-frequency 4000-4063; field site one to operate at center frequency (minus 10 ke) bend 3155-3240 ke; field site two to operate at center frequency (plus 10 ke) bend 3155-3240 kc; field site two to operate at center frequency (plus 10 ke) bend 3155-3240 kc. b. Off is to be requested to provide necessary backstop with FCC in this regard. 5. Nodus operand: a. For test measurement purposes MCS will transmit: (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a								
alternately the limitation beyond which the system cannot be established for operational assignments. b. In this connection, some of the inherent bandwidth requirements of the test units currently conceived. Little factual consideration has been taken towards the reduction of these acute problems. It has been, therefore, mecessary for the Agency representatives to confine for Task Order VI, to the arrangement of the equipments to parmit the establishment of valid measurements with which the Agency can then program into the necessary parameters for an operational acceptable system. 4. Future Action: (1) (In consideration of prior frequency data coordinated with AMB) to establish ECS terminal to operate at center-frequency hood-hof3; field site one to operate at center frequency (minus 10 kg) band 3155-32ko kg; field site two to operate at center frequency (plus 10 kg) band 3155-32ko kc. b. ddf is to be requested to provide necessary backstop with FCC in this regard. 5. Nodus operand: a. For test measurement purposes ECS will transmit: (1) A sine wave reedy signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a								
b. In this connection, sware of the inherent bandwidth requirements of the test units currently conceived. Little factual consideration has been taken towards the reduction of these acute problems. It has been, therefore, necessary for the Agency representatives to confine for Task Order VI, to the arrangement of the equipments to permit the establishment of valid measurements with which the Agency can then program into the necessary parameters for an operational acceptable system. 4. Future Action: a. For the purpose of conduction of the test, has been advised; (1) (In consideration of prior frequency data coordinated with AAB) to establish MCB terminal to operate at center-frequency \$1000-\$163; field site one to operate at center frequency (mims 10 ke) band \$155- \$250 ke; field site two to operate at center frequency (plus 10 ke) band \$155- \$250 ke. b. 665 is to be requested to provide necessary backstop with FCC in this regard. 5. Nodus operandi: a. For test measurement purposes MCS will transmit: (1) A sine wave reedy signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a								
b. In this connection, sware of the inherent bandwidth requirements of the test units currently conceived. Little factual consideration has been taken towards the reduction of these soute problems. It has been, therefore, necessary for the Agency representatives to confine for Task Order VI, to the arrangement of the equipments to parmit the establishment of valid measurements with which the Agency can then program into the necessary parameters for an operational acceptable system. 4. Future Action: a. For the purpose of conduction of the test, has been savised; (1) (In consideration of prior frequency data coordinated with ARB) to establish MCB terminal to operate at center-frequency \$000-\$063; field site one to operate at center frequency (nimus 10 ke) bend 3155- 3240 ke; field site two to operate at center frequency (plus 10 ke) bend 3155- 3240 ke. b. Off is to be requested to provide necessary backstop with FCC in this regard. 5. Notus operandi: a. For test measurement purposes MCS will transmit: (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a			alternately the limitation beyond which the system					
source of the inherent bandwidth requirements of the test units currently conceived. Little factual consideration has been taken towards the reduction of these souts problems. It has been, therefore, necessary for the Agency representatives to confine for Task Order VI, to the arrangement of the equipments to permit the establishment of valid measurements with which the Agency can then program into the necessary parameters for an operational acceptable system. 4. Future Action: a. For the purpose of conduction of the test, has been advised; (1) (In consideration of prior frequency data coordinated with AAB) to establish KCB terminal to operate at center-frequency 4000-4063; field site one to operate at center frequency (nims 10 kc) bend 3155-3240 kc; field site two to operate at center frequency (plus 10 kc) bend 3155-3240 kc. b. Aprils to be requested to provide necessary backstop with FCC in this regard. 5. Nodus operandi: a. For test measurement purposes ECS will transmit: (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a			cannot be established for operational assignments.					
test units currently conceived. Little factual consideration has been taken towards the reduction of these soute problems. It has been, therefore, necessary for the Agency representatives to confine for Task Order VI, to the arrangement of the equipments to parmit the establishment of valid measurements with which the Agency can then program into the necessary parameters for an operational acceptable system. 4. Future Action: a. For the purpose of conduction of the test, has been advised; (1) (In consideration of prior frequency data coordinated with AAB) to establish NCB terminal to operate at center-frequency \$4000-\$4063; field site one to operate at center frequency (nims 10 kg) bend \$155-\$250 kg; field site two to operate at center frequency (plus 10 kg) bend \$155-\$250 kg. b. Off is to be requested to provide necessary backstop with FCC in this regard. 5. Notus operand: a. For test measurement purposes NCS will transmit: (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a	;	ъ.						
consideration has been taken towards the reduction of these acute problems. It has been, therefore, mecessary for the Agency representatives to confine for Task Order VI, to the arrangement of the equipments to parmit the establishment of valid measurements with which the Agency can then program into the necessary parameters for an operational acceptable system. 4. Future Action: a. For the purpose of conduction of the test, has been advised: (1) (In consideration of prior frequency data coordinated with AAB) to establish MCS terminal to operate at center-frequency 4000-4063; field site one to operate at center frequency (nims 10 kg) bend 3155-3240 kg; field site two to operate at center frequency (plus 10 kg) band 3155-3240 kg. b. Off is to be requested to provide necessary backstop with FOC in this regard. 5. Notus operand: a. For test measurement purposes MCS will transmit: (1) A sine wave ready signal. (2) A pulse-train ensemble signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a								
of these scute problems. It has been, therefore, mecessary for the Agency representatives to confine for Task Order VI, to the arrangement of the equipments to parmit the establishment of valid measurements with which the Agency can then program into the mecessary parameters for an operational acceptable system. 4. Puture Action: a. For the purpose of conduction of the test, has been advised: (1) (In consideration of prior frequency data coordinated with AAB) to establish ECS terminal to operate at center-frequency \$4000-\$663; field site one to operate at center frequency (minus 10 ke) bend \$155-32\$0 ke; field site two to operate at center frequency (plus 10 ke) band \$155-32\$0 ke. b. edf is to be requested to provide necessary backstop with FCC in this regard. 5. Notus operand: a. For test measurement purposes ECS will transmit: (1) A sine wave ready signal. (2) A pulse-train ensemble signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a								
for Task Order VI, to the arrangement of the equipments to permit the establishment of valid measurements with which the Agency can then program into the necessary parameters for an operational acceptable system. 4. Puture Action: a. For the purpose of conduction of the test, has been advised: (1) (In consideration of prior frequency data coordinated with AAB) to establish NCB terminal to operate at center-frequency 4000-4063; field site one to operate at center frequency (minus 10 kc) bend 3155- 3240 kc; field site two to operate at center frequency (plus 10 kc) band 3155- 3240 kc. b. 645 is to be requested to provide necessary backstop with FCC in this regard. 5. Notus operand: a. For test measurement purposes NCS will treasure: (1) A sine wave ready signal. (2) A pulse-train execute signalthis signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a			consideration has been taken towards the reduction					
the arrangement of the equipments to parmit the establishment of valid measurements with which the Agency can then program into the necessary parameters for an operational acceptable system. 4. Future Action: a. For the purpose of conduction of the test, has been advised: (1) (In consideration of prior frequency data coordinated with AAB) to establish MCB terminal to operate at center-frequency \$1000-\$1063; field site one to operate at center frequency (minus 10 kc) band 3155- 32\$0 kc; field site two to operate at center frequency (plus 10 kc) band 3155- 32\$0 kc. b. \$4\$ is to be requested to provide necessary backstop with FCC in this regard. 5. Noins operand: (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a			of these acute problems. It has been, therefore,					
the arrangement of the equipments to parmit the establishment of valid measurements with which the Agency can then program into the necessary parameters for an operational acceptable system. 4. Future Action: a. For the purpose of conduction of the test, has been advised: (1) (In consideration of prior frequency data coordinated with AAB) to establish MCB terminal to operate at center-frequency \$1000-\$1063; field site one to operate at center frequency (minus 10 kc) band 3155- 32\$0 kc; field site two to operate at center frequency (plus 10 kc) band 3155- 32\$0 kc. b. \$4\$ is to be requested to provide necessary backstop with FCC in this regard. 5. Noins operand: (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a			necessary for the Agency representatives to confine					
the arrengement of the equipments to permit the establishment of valid measurements with which the Agency can then program into the necessary parameters for an operational acceptable system. 4. Puture Action: a. For the purpose of conduction of the test, has been advised; (1) (In consideration of prior frequency data coordinated with AAB) to establish MCB terminal to operate at center-frequency \$1000-\$063; field site one to operate at center frequency (minus 10 ke) band 3155- 32%0 ke; field site two to operate at center frequency (plus 10 ke) band 3155- 32%0 ke. b. \$4\$\$ is to be requested to provide necessary backstop with FCC in this regard. 5. Moins operand: (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a								
establishment of valid measurements with which the Agency can then program into the necessary parameters for an operational acceptable system. 4. Puture Action: a. For the purpose of conduction of the test, has been advised: (1) (In consideration of prior frequency data coordinated with AAB) to establish MCB terminal to operate at center-frequency 4000-4063; field site one to operate at center frequency (minus 10 ke) band 3155-3240 ke; field afte two to operate at center frequency (plus 10 ke) band 3155-3240 ke. b. 44 is to be requested to provide necessary backstop with FCC in this regard. 5. Nodus operandi: a. For test measurement purposes MCS will transmit: (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a		L	•					
Agency can then program into the necessary parameters for an operational acceptable system. 4. Puture Action: a. For the purpose of conduction of the test, has been advised: (1) (In consideration of prior frequency data coordinated with AAB) to establish MCB terminal to operate at center-frequency \$6000-\$663; field site one to operate at center frequency (minus 10 kg) bend 3155-3250 kg; field site two to operate at center frequency (plus 10 kg) bend 3155-3250 kg. b. diff is to be requested to provide necessary backstop with FCC in this regard. 5. Nodus operandi: a. For test measurement purposes MCS will transmit: (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a								
for an operational acceptable system. 4. Puture Action: a. For the purpose of conduction of the test, has been advised: (1) (In consideration of prior frequency data coordinated with AAB) to establish MCB terminal to operate at center-frequency 4000-5063; field site one to operate at center frequency (mims 10 ke) bead 3155-3240 ke; field site two to operate at center frequency (plus 10 ke) band 3155-3240 ke. b. Off is to be requested to provide necessary backstop with FCC in this regard. 5. Nodus operand: a. For test measurement purposes MCS will transmit: (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a								
A. For the purpose of conduction of the test,								
a. For the purpose of conduction of the test, has been advised:								
(1) (In consideration of prior frequency data coordinated with AAB) to establish MCB terminal to operate at center-frequency \$000-\$063; field site one to operate at center frequency (minus 10 kg) band 3155-3240 kg; field site two to operate at center frequency (plus 10 kg) band 3155-3240 kg. b. 645 is to be requested to provide necessary backstop with FCC in this regard. 5. Notus operandi: a. For test measurement purposes MCS will transmit: (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a	4.	Pata	re Action:					
(1) (In consideration of prior frequency data coordinated with AAB) to establish MCB terminal to operate at center-frequency \$000-\$063; field site one to operate at center frequency (mims 10 kc) band 3155-3240 kc; field site two to operate at center frequency (plus 10 kc) band 3155-3240 kc. b. 645 is to be requested to provide necessary backstop with FCC in this regard. 5. Notus operandi: a. For test measurement purposes MCS will transmit: (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a		a.	For the purpose of conduction of the test,					
ecordinated with AAB) to establish MCB terminal to operate at center-frequency 4000-4063; field site one to operate at center frequency (minus 10 ke) bend 3155- 3240 ke; field site two to operate at center frequency (plus 10 ke) band 3155- 3240 ke. b. 645 is to be requested to provide necessary backstop with FCC in this regard. 5. Nodus operandi: a. For test measurement purposes MCS will transmit: (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a			has been advised;					
ecordinated with AAB) to establish MCB terminal to operate at center-frequency 4000-4063; field site one to operate at center frequency (minus 10 ke) bend 3155- 3240 ke; field site two to operate at center frequency (plus 10 ke) band 3155- 3240 ke. b. 645 is to be requested to provide necessary backstop with FCC in this regard. 5. Nodus operandi: a. For test measurement purposes MCS will transmit: (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a								
ecordinated with AAB) to establish MCB terminal to operate at center-frequency 4000-4063; field site one to operate at center frequency (minus 10 ke) bend 3155- 3240 ke; field site two to operate at center frequency (plus 10 ke) band 3155- 3240 ke. b. 645 is to be requested to provide necessary backstop with FCC in this regard. 5. Nodus operandi: a. For test measurement purposes MCS will transmit: (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a			(1) (In consideration of prior frequency data					
terminal to operate at center-frequency 4000-4063; field site one to operate at center frequency (minus 10 kc) bend 3155- 3240 kc; field site two to operate at center frequency (plus 10 kc) bend 3155- 3240 kc. b. 645 is to be requested to provide necessary backstop with FCC in this regard. 5. Nodus operandi: a. For test measurement purposes NCS will transmit: (1) A sine wave ready signal. (2) A pulse-train execute signalthis signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a								
4000-4063; field site one to operate at center frequency (mimus 10 kc) band 3155-3240 kc; field site two to operate at center frequency (plus 10 kc) band 3155-3240 kc. b. 645 is to be requested to provide necessary backstop with FCC in this regard. 5. Notus operandi: a. For test measurement purposes NCS will transmit: (1) A sine wave reedy signal. (2) A pulse-train execute signalthis signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a			•					
center frequency (minus 10 ke) bend 3155- 3240 ke; field site two to operate at center frequency (plus 10 ke) band 3155- 3240 ke. b. 645 is to be requested to provide necessary backstop with FCC in this regard. 5. Nodus operandi: a. For test measurement purposes NCS will transmit: (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a								
3240 kc; field site two to operate at center frequency (plus 10 kc) band 3155-3240 kc. b. 645 is to be requested to provide necessary backstop with FCC in this regard. 5. Notus operandi: a. For test measurement purposes NCS will transmit: (1) A sine wave reedy signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a								
center frequency (plus 10 kc) band 3155- 3240 kc. b. diff is to be requested to provide necessary backstop with FCC in this regard. 5. Notus operandi: a. For test measurement purposes NCS will transmit: (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a								
 3240 kc. b. 645 is to be requested to provide necessary backstop with FCC in this regard. 5. Notus operandi: a. For test measurement purposes ECS will transmit: (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a 								
 b. dis is to be requested to provide necessary backstop with FCC in this regard. 5. Nodus operandi: a. For test measurement purposes NCS will transmit: (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a 								
with FCC in this regard. 5. Notus operandi: a. For test measurement purposes WCS will transmit: (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a			. Jean ge.					
with FCC in this regard. 5. Notus operandi: a. For test measurement purposes WCS will transmit: (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a			all in as he municipal in municipal management hashes an					
5. Notus operandi: a. For test measurement purposes NCS will transmit: (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a		•						
a. For test measurement purposes MCS will transmit: (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a			Area loc in core lefinis.					
 (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a 	5.	Note	s operandi:					
 (1) A sine wave ready signal. (2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a 		,						
(2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a		8-	For test measurement purposes MCS will transmit:					
(2) A pulse-train execute signal—this signal will be not more than 10 pulses in duration, pulses will be square wave in nature and will have a			(1) A sine wave reedy signal.					
be not more them 10 pulses in duration, pulses will be square wave in nature and will have a								
will be square wave in nature and will have a			(2) A pulse-train execute signalthis signal will					
will be square wave in nature and will have a			be not more than 10 pulses in duration, pulses					
parse duration or 174 microsecome.			pulse duration of 154 microseconds.					

SECRET CONVENIENT AL

Page 3

12 September 1955

- (3) NCS will not transmit these pulse trains (for test/measurement purposes) at intervals of less than 3 minutes apart.
- (4) Field stations will transpond with single pulse units.
- (5) Antenna rediction will be high angle, half wave doublet at about 30-35 foot above ground or 1/10th wave above reflector.
- (6) Initial operation will be (by reason of frequency and band-width considerations) restricted to daytime operation until initial measurements have been evaluated.

50X1

OC-2/863-27/13R:mmb (12 September 1955)

CC: Rab Subject File

Monthly Report File (2)

Ber-ep

SPA

SECRET